



Class III Biological Safety Cabinet

Class III Biosafety Cabinet is totally enclosed and gas-tight with ULPA filtered supply and exhaust air. Work is performed with long-sleeved gloves. The cabinet is kept under negative pressure of at least 120 Pa, and airflow is maintained by a dedicated exterior exhaust system. It can protect the operator, product and environment.



<http://www.sco-tech.com>





**Class III
Biological
Safety Cabinet**



ADVANTAGE

1. With memory function in case of power-failure.
2. UV lamp ensures work area sterilization effectively.
3. An angled cabinet front ensures an ergonomic working posture.
4. Exhaust air is double-filtered through high-quality HEPA filters with typical efficiency of 99.999% for 0.3µm particles.

TECHNICAL PARAMETERS


| Model | LF-III 154 | LF-III 179 |
|----------------------|---|------------------|
| External Size(W*D*H) | 1540*880*2000 mm | 1790*880*2080 mm |
| Internal Size(W*D*H) | 910*650*660 mm | 1165*650*660 mm |
| Pass Box Size(W*D*H) | Internal Size:430*330*355mm External Size:575*425*495mm | |
| Gloves | One pair of 800mm butyl rubber gloves | |
| Front Window | 8 mm toughened glass, anti-ultraviolet radiation | |
| Display | LCD display | |
| Pre-Filter | Polyester fiber, washable | |
| Pressure | ≥ negative120 Pa | |
| HEPA Filter | Air supply filter: Efficiency 99.999% at 0.3µm First exhaust filter: Efficiency 99.999% at 0.3µm Second exhaust filter: Efficiency 99.999% at 0.3µm | |
| Noise | NSF 49 ≤ 61dB / EN 12469 ≤ 48dB | |
| Alarm | Audio and visual alarm, abnormal pressure; filter replacement | |
| Work Zone Material | 304 stainless steel | |
| Illumination | ≥ 1000Lux | |
| Consumption | 1200W | 1300W |
| LED Lamp | 12W*2 | 16W*2 |
| UV Lamp | 18W*2, 8W*1 | 30W*2, 8W*1 |
| | Emission of 253.7 nanometers for most efficient decontamination | |
| Power Supply | AC220V±10%, 50/60Hz; 110V±10%, 60Hz | |
| Gross Weight | 350kg | 450kg |
| Package Size(W*D*H) | 1635*1062*2160mm | 1890*1065*2240mm |
| Standard Accessories | Gloves, fluorescent lamp, UV lamp*4, remote control, pressure meter, drain valve | |



Pass Box
Double doors with interlock function and UV lamp.



Pressure Meter
Display the pressure of work zone.



UV Lamp
Emission of 253.7 nanometers for most efficient decontamination.



LCD Display
Large display is easy to monitor the pressure parameters for work zone and three filters.

