

Manual Rotary Microtome

Model: MT-315



Œ

MT-315 Rotary Microtome is ideal for most routine histology, biological and industrial applications. In order to ensure top quality performance and precision in the preparation of microtome sections the MT-315 features key component parts from Japan, and due to this high precision and stability you can ensures exact reproducible section quality in wax and plastic embedded sections. This is a complete kit include all important accessories.

FEATURES:

- A high precision specimen feed
- A universal cassette clamp and standard specimen clamp
- > The dual fail-safe control system ensures safe and reliable use for changing the blade or tissue block.
- The special blade holder, conveniently allows the use of a disposable blade for safer use. additionally helps the durability of the disposable blade.

This

- > Smoothly running handwheel which can be locked in any position or highest position
- Spacious, integrated section waste tray

TECHNICAL DATA

Type of microtome :	Mechanical	
Section thickness setting range:	0 - 60 μm	
Setting values :	From 0 - 2 μm	in 0.5 μm increments
	Form 2 - 10 μm	in 1.0 μm increments
	Form 10 - 20 μm	in 2.0 μm increments
	Form 20 - 60 μm	in 5.0 μm increments
Horizontal specimen stroke:	28 mm	
Vertical specimen stroke:	60 mm	
Precision error:	± 5%	
Sample orientation:	8° along the X-Y-axis, rotable 360°	
Maximum section size:	50 × 45mm	
Dimensions incl. tray(L/T/H):	300 x 570 x 270 mm (L x W x H)	
Net weight:	Approx. 34 kg	

Standard Accessories (included)

Blade Carrier, Waste Tray, 2 types of clamp, 4 Tissue molds & 50 Cassettes

Optional Accessories (not included)













Trimming Handel