

## Fume Hood



**LED Display**  
Digital LED display:  
Airflow Level



**Water Remote Control**



**Waterproof Socket**



**Water Tap**



**Universal Wheel**



**Water Tap & Water Sink**



## ADVANTAGE

- Adjustable air speed: 9 levels.
- Resistant to moderate acid and alkali.
- With memory function in case of power-failure.
- Manual front glass window, height adjustable.
- With air velocity memory function in case of power failure.
- PP Built-in axial flow blower, melamine board inward, resistant to acid, alkali, and anti-corrosion.

## TECHNICAL PARAMETERS

Model	FH-100	FH-120	FH-150	FH-180	
External Size(W*D*H)	1000*800*2365mm	1200*800*2365mm	1500*800*2465mm	1800*800*2465mm	
Internal Size(W*D*H)	790*635*820mm	990*635*820mm	1290*635*820mm	1590*635*820mm	
Work Surface Height	900mm				
Max Opening	750mm				
Air Velocity	0.3~0.8m/s				
Noise	≤60dB				
Exhaust Duct	PVC, Standard length: 4 meters φ300mm				
Pipe Strap	2 pcs	2 pcs	2 pcs	4 pcs	
LED Lamp	8W*1	12W*1	16W*1	16W*1	
Blower	PP Built-in axial flow blower; Speed adjustable		PP Built-in centrifugal blower; Speed adjustable		
Front Window	Manual, 5mm toughened glass, height adjustable				
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz				
Consumption	400W	400W	500W	500W	
Material	Exterior	1.0mm cold-rolled steel with bacteria power coating.			
	Interior	High grade melamine board with good acid and alkali resistance function			
	Work table	Chemical resistant phenolic resin			
Standard Accessory	Water tap, Water sink, Waterproof socket*2, LED lamp, PP Built-in axial flow blower, Total load of 2 waterproof sockets: 500W, 4 meters PVC exhaust duct, pipe strap				
Optional Accessory	Gas tap				
Gross Weight	286kg	317kg	350kg	400kg	
Package	Main Body	1140*940*1720mm	1340*940*1720mm	1640*940*1720mm	1940*940*1720mm
	Base Cabinet	1140*940*1050mm	1340*940*1050mm	1640*940*1050mm	1940*940*1080mm