

AEL 900 Electrolyte Analyzer

Parameter configuration:

A K, Na, Cl
B K, Na, Cl, TCO₂, Ag
C K, Na, Cl, iCa, nCa, TCa, pH
D K, Na, Cl, iCa, nCa, TCa, pH, TCO₂, Ag
F K, Na, Cl, Li
H K, Na, Cl, iCa, nCa, TCa, pH, Li
I K, Na, Cl, iCa, nCa, TCa, pH, Li, TCO₂, Ag
J K, Na, Cl, Mg
K K, Na, Cl, iCa, nCa, pH, Mg
L K, Na, Cl, iCa, nCa, TCa, pH, Mg, TCO₂, Ag
M K, Na, Cl, iCa, nCa, TCa, pH, Li, Mg, TCO₂, Ag

Specification:

Sample: serum, plasma, whole blood,
cerebrospinal fluid and dilute urine
Analysis Method: ion selective electrode (ISE)

Measuring speed: ≤25s
Sample volume: 60-300ul (item 3 to item 11)
Sample position: 39 positions (including 5
emergency and 2 QC)
Storage: up to 10000 test results
Printer: Internal thermal printer
Interface: RS232 port

Working environment:

Temperature: 5-40°C
Relative Humidity: ≤ 80 %
Atmospheric pressure: (86~106) kPa
Power supply: AC220V±22V, 50Hz±1Hz
Power: ≤ 120W

Dimension: 340mm*200mm*380mm
Net weight: 6Kg

Main Features:

- Human-machine interactive menu; Dynamic and real-time display of sample ID.
- Liquid level automatic detection and alarming. Real-time diagnostic of system working status.
- Automatically detect and filter tiny bubbles to avoid clog and ensure accurate measurement.
- Wave theory flushing method and direct flushing pipe method to avoid block and crossed contamination.
- Automatic calibration and two-point correction to adjust slope and intercept; Available to print-out QC graph and QC statistical parameters.
- Power failure protection to avoid data losing. Data storage could be extended to more than 50000. Supporting fuzzy query.
- Supporting LIS software; Upload data format is selectable; Supporting RTC Clock management.
- Available to power off any time, therefore reduce reagent consumption, suitable for any hospitals.



A+A Diagnostics GmbH



AEL 900 Electrolyte Analyzer

- 7" Color touch screen, easy to operate
- High accurate and long life electrode and TCO₂ sensor
- Programmable multi-format print-out
- Reagent pack, real time monitoring of reagent residual volume
- Up to 50,000 test results can be stored
- RS-232 port, supporting bar code reader and USB interface
- Sleep mode to reduce reagent consumption
- Option: Sample tray

<http://www.aa-diagnostics.de>