

Safety
Efficiency
Environment friendly



Features:



- Manufactured in accordance with EN12469:2000 standard
- State of the art microprocessor control system
- Main switch with removable key
- Soft touch keyboard
- Bar graph for exhaust air flow conditions; permanent display
- Alarms for low air flow
- Sloped front for the most comfortable access
- Front and side access for filter maintenance and service
- C-shaped support stand for easy one man installation procedure
- Transfer hatch with interlocked doors (right or left positioned)
- Class III cabinet with exclusive three filter design and Class 100 inner chamber.
- Two comfortable sizes (1.2 mt and 1.8 mt)

Features:

The main specifications...

- Controls comfortably located at eye level
- Fan speed and aeraulic controlled by Microprocessor
- Three operating modes: normal, stand-by, calibration
- High speed rinse at start up
- Self calibration and internal Watch-dog cycle before "SAFE" condition is reached
- Visual display of "SAFE" conditions and "UNSAFE" conditions (LED and bar graph)
- Elapsed time meter
- Microprocessor control with following specifications:
 - Multilevel alarms, with redundancy functions.
 - Permanent display of working conditions.
 - High air flow stability both in case of transitional disturbances or to progressive filter clogging
 - Power failure alarm
- Volt-free contact for remote monitoring of exhaust fan.
- Automatic reset of initial conditions in case of power failure
- C-shaped support stand for easy one man installation procedure
- Anti blow back valve (optional) for ducted configuration
- Magnehelic Gauge for internal chamber pressure constant monitoring
- One (1) Electrical Socket (1.2), two (2) Electrical Socket (1.8 size) as standard option.
- UV-Light installed on top (standard option)

Mechanical and functional specifications...

- Sloped front design for the highest operational comfort.
- Stainless Steel internal surfaces with 2B finishing
- Liquid retaining work surface (Stainless Steel 2B finishing)
- Total visibility air and aerosol-tight front window equipped with robust gloves (Class III) for the safest operation when working with Risk Group 4 pathogens.
- Class III: Exclusive four filter design for the highest safety of the environment and the operator (Risk Group 4 pathogens):
 - one (1) prefilter, one (1) HEPA H14 In-Let,
 - two (2) HEPA H14 Exhaust Filters
- H14 class High Efficiency Particulate Air filters with 99.995% efficiency on MPPS (most penetrating particle size) (EN1822-1 and EN 13091:1999 tested and certified)
- Filter change and maintenance from the front of the cabinet.
- Exhaust transitions easily installable.
- Anti-blow-back valve available as add-on option

- Key operated. The key can be removed when the unit is in SAFE mode, in order to avoid unwanted operation. In case of power failure, the cabinet is re-set to original working conditions.
- Self calibration cycle performed when cabinet is switched on.
- High speed rinse and set up cycle performed, before reaching the SAFE operating mode.
- Visual display of SAFE conditions. Pre-warning before actual alarm conditions are reached (visual and acoustic alarms)
- Soft touch control with keys for standard service utilities. Interconnected UV and fluorescent lights.
- 100% air exhaust.
- Light intensity on work surface > 1000 lux.
- Noise level ≤58 dB(A) [1.2 size]
- Work surface displacement (vibration) <0.005mm RMS between 20Hz and 20,000Hz (ISO 5349 tested and certified)
- 230V, 50Hz (230V,60Hz also available)
- Max power (for each power point): 3Amps.
- Microprocessor equipped with analogical watch-dog.
- Leakage tested in agreement with EN 12469 and ISO10648.2
- CE certification according to Machinery Directive 2006/42/CEE.



Specifications:

	S@fe ³ 1.2	S@fe ³ 1.8
Work chamber dimensions (W x D x H) mm	2015 x 822 x 1300	2565 x 822 x 1300
External dimensions (W x D x H) mm	1200 x 660 x 700	1750 x 660 x 700
N° of glove ports	2	4
Exhaust air flow rate (m ³ /h)	> 180 m ³ /h	> 180 m ³ /h
Internal Differential pressure	< -220 Pa	< -220 Pa
Weight	210 kg	270 kg
Power supply	220/240 V - 50 Hz	220/240 V - 50 Hz
Power	500 W	1000 W
Noise level	< 58 dB(A)	< 58 dB(A)
Lighting	> 1000 Lux	> 1000 Lux
Order No.	0.380.120	0.380.180
Accessories:		
Stand	0.380.121	0.380.181

*These Microbiological Safety Cabinets, are
manufactured according to EN12469:2000*



Address, S C O - T e c h
Auf der Heide 15
D-37351 Dingelstädt
Federal Republic of Germany

Phon: + 49 (0) 36075 / 43439-0
Fax: + 49 (0) 36075 / 43439-9
E-mail: sco@sco-tech.com
Internet: www.sco-tech.com

Contact